

Container dimensions

		ISO 668 (1995)												
Designation		45'		40'				30'				20'		
		1EE	1EEE	1A	1AA	1AAA	1AX	1B	1BB	1BBB	1BX	1C	1CC	1CX
Height	ft	8'6"	9'6"	8'	8'6"	9'6"	<8'	8'	8'6"	9'6"	<8'	8'	8'6"	<8'
	H mm	2591 ^{0/-5}	2896 ^{0/-5}	2438 ^{0/-5}	2591 ^{0/-5}	2896 ^{0/-5}	<2438	2438 ^{0/-5}	2591 ^{0/-5}	2896 ^{0/-5}	<2438	2438 ^{0/-5}	2591 ^{0/-5}	<2438
Length	L	ft	45'	40'				29'11 1/4"				19'10 1/2"		
		mm	13716 ^{0/-10}	12192 ^{0/-10}				9125 ^{0/-10}				6058 ^{0/-6}		
	S	mm	13509 ^{+4/-6}	11985 ^{+4/-6}				8918 ^{+4/-6}				5853 ^{+3/-5}		
	C ₁	mm	101.5 ^{0/-1,5}											
Width	W	ft	8'											
		mm	2438 ^{0/-5}											
	P	mm	2259 ^{0/-5}											
	C ₂	mm	89 ^{0/-1,5}											
Difference D1-D2		≤ 19mm		≤ 19mm				≤ 16mm				≤ 13mm		
max. grossmass kg		30480		30480				25400				24000		

